



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEX PTB 08.0005U	Issue No: 2	Certificate history:
Status:	Current	Page 1 of 4	Issue No. 2 (2016-09-08)
Date of Issue:	2016-09-08		Issue No. 1 (2012-02-29)
Applicant:	ROSE Systemtechnik GmbH Erbeweg 13 32457 Porta Westfalica Germany		Issue No. 0 (2008-03-07)
Equipment:	Empty Enclosure Type 25.*****		
Optional accessory:			
Type of Protection:	Increased Safety "eb", Protection by enclosures "tb"		
Marking:	Ex eb IIC Gb Ex tb IIIC Db		

Approved for issue on behalf of the IECEx
Certification Body:

Dr.-Ing. Detlev Markus

Position:

Head of Working Group "Flame Transmission Processes"

Signature:
(for printed version)

Date:

27.09.16

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).

Certificate issued by:

Physikalisch-Technische Bundesanstalt (PTB)
Bundesallee 100
38116 Braunschweig
Germany





IECEX Certificate of Conformity

Certificate No: IECEX PTB 08.0005U Issue No: 2
Date of Issue: 2016-09-08 Page 2 of 4
Manufacturer: ROSE Systemtechnik GmbH
Erbeweg 13
32457 Porta Westfalica
Germany

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition:6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-31 : 2013 Edition:2	Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
IEC 60079-7 : 2015 Edition:5.0	Explosive atmospheres – Part 7: Equipment protection by increased safety "e"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[DE/PTB/ExTR08.0004/02](#)

Quality Assessment Report:

[DE/TUR/QAR09.0009/06](#)



IECEX Certificate of Conformity

Certificate No: IECEx PTB 08.0005U

Issue No: 2

Date of Issue: 2016-09-08

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

Description

Empty enclosure type 25.*****, made of aluminium, which may be provided with flanges and a glass or plastic inspection window.

Technical Data, Nomenclature and Schedule of Limitations see attachment.

CONDITIONS OF CERTIFICATION: NO



IECEX Certificate of Conformity

Certificate No: IECEx PTB 08.0005U

Issue No: 2

Date of Issue: 2016-09-08

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

- 1) New test according to IEC 60079-0:2011, IEC 60079-7:2015, IEC 60079-31:2013
- 2) New marking.

Annex:

[COCA08.0005U-02.pdf](#)



Applicant: ROSE Systemtechnik GmbH
Erbeweg 13
32457 Porta Westfalica
Germany

Electrical Apparatus: Empty Enclosure Type 25.*****

Description of equipment

Empty enclosure type 25.*****, made of aluminium, which may be provided with flanges and a glass or plastic inspection window.

Technical data

sizes	length	width	depth
min	58 mm	64 mm	34 mm
max	600 mm	600 mm	227 mm

Ambient temperature

- 55 °C to +135 °C with Silicon gasket
- 40 °C to +100 °C with HF gasket
- 40 °C to +100 °C with PU-foam
- 20 °C to + 85 °C with CR gasket
- 20 °C to +100 °C with window out of glas
- 50 °C to +100 °C with PC-window mono duro clear 8099, conductive

Protection against contact, foreign bodies and water

IP 66 acc. to IEC 60529

Nomenclature

25.	**	**	**
1	2	3	4

- 1: Material aluminium
- 2: Height
- 3: Width
- 4: Depth

Schedule of limitations

The empty enclosure with a coating must not be used in areas affected by charge-producing processes, mechanical friction and separation processes, electron emission (e.g. in the vicinity of electrostatic coating equipment), and pneumatically conveyed dust.

Installation of electrical components requires a further assessment by an ExCB.

Physikalisch-Technische Bundesanstalt (PTB)

Bundesallee 100, 38116 Braunschweig, Germany
Postfach 33 45, 38023 Braunschweig, Germany
Telephone +49 531 592-0, Telefax +49 531 592-3605

IECEX Technical Report: DE/PTB/ExTR08.0004/02 details

ExTR :	
ExTR Reference Number*: (automatic numbering)	DE/PTB/ExTR08.0004/02
Status*:	Issued
ExTR Free Reference Number*:	DE/PTB/ExTR08.0004/00
Date of Issue*: (yyyy-mm-dd)	2016-09-08
Details of change*:	New test according to IEC 60079-0:2011, IEC 60079-7:2015, IEC 60079-31:2013 and changing of the marking.
List of Standards Covered*:	IEC 60079-0 (Ed.6.0); IEC 60079-31 (Ed.2); IEC 60079-7 (Ed.5.0)
Issuing ExTL*:	PTB - Physikalisch-Technische Bundesanstalt (PTB)
Endorsing ExCB*:	PTB - Physikalisch-Technische Bundesanstalt (PTB)
Manufacturer*:	ROSE Systemtechnik GmbH + Co. KG Erbeweg 13 - 15 32457 Porta Westfalica
Country of Manufacture*:	Germany
Ex Protection*:	Increased Safety "eb" Protection by Enclosures "tb"
Ratings:	see certificate
Equipment*:	Empty Enclosure
Model Reference*:	Type 25.*****
Related IECEX Certificates:	IECEX PTB 08.0005U issue: 2 [Current]
Comment:	
Attachment:	

Last modified: 06.09.2016 13:28:19

Copyright © IEC-IECEX 2016 , Geneva, Switzerland. All rights reserved.